

Aficio® 1060 & 1075

Versatile Document Management ...
Copy/Print Systems



RICOH®

Aficio® 1060 & 1075



Specifications

General Specifications

Printing Process:	Four laser beams and electro-photographic printing
Configuration:	Console
Standard Memory:	128 MB/40 GB
Warm Up Time:	5 minutes
Quantity Indicator:	1 to 999
Power Source:	120V/60Hz/20A
Dimensions (WxDxH):	28" x 30" x 47"
Weight:	441 lbs.

Paper Supply

Paper Feed:	1st Tray: 1,550 sheets x 2 (tandem) 2nd and 3rd Tray: 550 (User Adjustable)
Paper Size:	5 1/2" x 8 1/2" to 12" x 18" through bypass
Bypass:	100 sheets
Paper Weight:	14 lb. Bond - 34 lb. Bond/14 lb. Bond - 110 lb. Index (Bypass-Thick Paper Mode)
Total:	4,300 sheets

System Specifications

Speed

First Copy:	3.5 seconds Face Up 5.3 seconds Face Down
Copying Speed:	Aficio 1060: 60 copies/minute - multiple sets (Letter/Legal) Aficio 1075: 75 copies/minute - multiple sets (Letter/Legal)
Copy Resolution:	True 1,200 x 1,200 dpi
Gray Scale:	256 levels

Original/Copy Size

Original Type:	Book/Sheet
Original Size:	Up to 11" x 17" (12" x 18" using Platen)
Copy Size:	5 1/2" x 8 1/2" to 11" x 17" (12" x 18" using Bypass Tray)

Reduction/Enlargement

Reproduction Ratios:	50%, 65%, 73%, 78%, 85%, 93%, 121%, 129%, 155%, 200%, 400%
Zoom:	25% - 400% in 1% increments

System Accessories

Automatic Document Feeder

Original Size:	5 1/2" x 8 1/2" to 11" x 17"
Original Paper Weight:	11 lb. Bond - 34 lb. Bond (simplex)/14 lb. Bond - 34 lb. Bond (duplex)
Original Stack Capacity:	100 sheets

LCT (Large Capacity Tray)

Paper Size:	8 1/2" x 11"
Paper Weight:	14 lb. Bond - 34 lb. Bond
Paper Capacity:	4,000 sheets (20 lb. Bond)
Dimensions (WxDxH):	12.6" x 18.3" x 26.4"
Weight:	Less than 44 lbs.

LG (8 1/2 x 14) Option with LCT

Paper Size:	8 1/2" x 14"
-------------	--------------

9-Bin Mailbox (option to be equipped with SR850 or SR860 Finisher)

No. of Bins:	9 bins
Stack Capacity Per Bin:	100 sheets
Paper Size:	5 1/2" x 8 1/2" to 11" x 17"
Dimensions (WxDxH):	22" x 24" x 27"
Weight:	Less than 33 lbs.

Copy Tray

Dimensions (WxDxH):	16" x 13.4" x 2.8"
Paper Capacity:	500 Sheets (8 1/2" x 11"); 250 Sheets (8 1/2" x 14", 11" x 17")
Weight:	1.41 lbs.

11 x 17 Tray Kit

Paper Size:	8 1/2" x 11", 8 1/2" x 14" SEF, 11" x 17" SEF
Dimensions (WxDxH):	20" x 8.6" x 21.4"
Paper Capacity:	1,000 sheets
Weight:	24.2 lbs.

Tab Sheet Holder

Dimensions (WxDxH):	11" x 4.5" x 2.8"
Weight:	.55 lbs.



RICOH DEPENDABLE

SR840 Finisher w/100 Sheet Stapler

Shift Tray	
Stack Capacity:	3,000 Sheets (8½" x 11"); 1,500 Sheets (8½" x 14", 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond - 110 lb. Index
Stack Capacity with Stapler	
Staple capacity per set:	2-100 Sheets (8½" x 11") 2-50 Sheets (8½" x 11" SEF, 8½" x 14", 11" x 17")
Staple Position:	Top, bottom, 2 staples, top slant
Proof Tray	
Stack Capacity:	500 Sheets (5½" x 8½" to 8½" x 11") 250 Sheets (8½" x 14" to 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond- 110 lb. Index
Dimensions (WxDxH):	31.5" x 28.7" x 38.6"
Weight:	143.3 lbs. (Finisher only)
Hole Punch Option: 2 or 3 holes user selectable	
Jogger Option: To be equipped with the SR840 Finisher	

SR850 Finisher w/50 Sheet Stapler

Shift Tray	
Stack Capacity:	3,000 Sheets (8½" x 11"); 1,500 Sheets (8½" x 14", 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond - 110 lb. Index
Staple Capacity	
Same Paper Size:	50 sheets (5½" x 8½" or 8½" x 11") 30 Sheets (8½" x 14" to 12" x 18")
Mixed Paper Size:	30 Sheets (5½" x 8½", 8½" x 11", 11" x 17")
Staple Position:	Top, bottom, 2 staples, top slant
Proof Tray	
Stack Capacity:	250 sheets (5½" x 8½" to 8½" x 11") 50 sheets (8½" x 14" to 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond - 90 lb. Index
Dimensions (WxDxH):	28" x 24.8" x 38.4"
Weight:	143 lbs. - with punch
Hole Punch Option: 2 or 3 holes user selectable	

SR860 50 Sheet Finisher with Saddle Stitch

Upper Shift Tray	
Paper Capacity:	500 Sheets (8½" x 11") 250 Sheets (8½" x 14", 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond - 110 lb. Index
Lower Shift Tray	
Paper Capacity:	2,500 sheets (8½" x 11 LEF) 1,250 Sheets (8½" x 11 SEF, 8½" x 14", 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond- 110 lb. Index
Staple Capacity	
Same Paper Size:	50 Sheets (5½" x 8½" or 8½" x 11") 30 Sheets (8½" x 14" or 12" x 18")
Mixed Paper Size:	30 Sheets (5½" x 8½, 8½" x 11", 11" x 17")
Saddle Stitch:	15 sheets (8½" x 11, 11" x 17")
Staple Position:	Top, bottom, 2 staples, top slant
Saddle Stitch Position:	Center 2 positions
Center Folding Without Stitch:	1 sheet

Proof Tray

Paper Capacity:	250 Sheets (5½" x 8½" or 8½" x 11") 50 Sheets (8½" x 14" to 12" x 18")
Paper Size:	5½" x 8½" to 12" x 18"
Paper Weight:	14 lb. Bond - 90 lb. Index
Dimensions (WxDxH):	28" x 24.8" x 38.4"

Hole Punch Option: 2 or 3 holes user selectable

Interposer (available with all 3 finishers)

Paper Size:	5½" x 8½" to 11" x 17"
Paper Weight:	17 lb. Bond - 110 lb. Index
Paper Capacity:	200 Sheets
Paper Set:	Center position
Dimensions (WxDxH):	20" x 24" x 8"
Weight:	26.4 lbs.

Print Controller Specifications*

Print Speed:	Aficio 1060: 60 prints/minute Aficio 1075: 75 prints/minute
CPU:	RM7000A, 375 MHz
Interface:	Parallel IEEE1284, Ethernet Network Interface Card 10/100BaseT (Standard); Wireless LAN, Interface USB 2.0, IEEE1394 (Optional)
Network Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Memory Capacity:	128 MB (Standard); 128 MB and 256 MB (Optional); (256 MB Memory required for printing)
Language:	RPCS (Refined Print Command Stream); PCL5e/PCL6 (Standard); Adobe PostScript3 (Optional)
Print Resolution:	RPCS: 300/600/1200 dpi; PCL5e: 300/600 dpi; PCL6: 600/1200 dpi; PS3: 300/600/1200 dpi
Drivers for PCL5e:	Windows 95/98/ME/2000/NT4.0/XP
Drivers for PCL6:	Windows 95/98/ME/2000/NT4.0/XP
Drivers for PS3:	Windows 95/98/ME/2000/NT4.0/XP Macintosh 8.6 or higher (excluding 10.0)
Utilities:	SmartNetMonitor
Drivers for RPCS:	Windows 95/98/ME/2000/NT4.0/XP

* DeskTopBinder comes bundled with Printer Kit or Printer/Scanner Kit.

Printer Accessories

(1) Printer/Scanner Kit; (2) Printer Kit; (3) Adobe PostScript3 Option;
(4) 128 MB Memory Option; (5) 256 MB Memory Option; (6) IEEE1394 I/F Option;
(7) USB 2.0 I/F Option; (8) Wireless LAN I/F Option

Scanner Specifications*

Scan Speed:	75 images/minute (Aficio 1060/1075)
-------------	-------------------------------------

Imaging

Optical Resolution:	600 dpi
Output Format:	PDF, TIFF, JPEG

Connectivity

Interface Support:	10/100BaseT (Standard); Wireless LAN - IEEE802.11b (Optional); IEEE1394 (Optional)
Bundled Drivers:	Network TWAIN

Scan to E-mail

Scan to E-Mail:	SMTP Gateway and TCP/IP required
Maximum Destination Addresses:	100
Maximum Stored Destination Addresses:	2,000

* Must order Printer/Scanner Kit for scan capabilities.

NOTES: Under Printer Accessories Item 1 and Item 2 cannot be installed together.
Additional Memory option, either Item 4 or Item 5 is mandatory for Item 1 and Item 2. Only one item out of Item 6, Item 7 and Item 8 can be installed.
Specifications subject to change without notice.

Aficio® 1060 & 1075

Configured to Meet Your Requirements

Copier Configuration



Shown with 50-Sheet Finisher and Interposer

- Aficio 1060 & 1075 System
- Large Capacity Tray
- Finisher
 - 50 Sheet (SR850)
 - 100 Sheet (SR840)
 - Saddle Stitch Finisher (SR860)
- 2 or 3 Hole Punch
- Interposer

Copier/Printer Configuration



Shown with Saddle Stitch Finisher and 9-Bin Mailbox

- Aficio 1060 & 1075 System
- Large Capacity Tray
- Finisher
 - 50 Sheet (SR850)
 - 100 Sheet (SR840)
 - Saddle Stitch Finisher (SR860)
- 2 or 3 Hole Punch
- 9-Bin Mailbox
- Printer Kit Type 1075
- Adobe PostScript3
- Memory (256 MB required for printing)
 - 128 MB
 - 256 MB
- DeskTopBinder

Copier/Printer/Scanner Configuration



Shown with 100-Sheet Finisher

- Aficio 1060 & 1075 System
- Large Capacity Tray
- Finisher
 - 50 Sheet (SR850)
 - 100 Sheet (SR840)
 - Saddle Stitch Finisher (SR860)
- 2 or 3 Hole Punch
- Interposer
- Printer/Scanner Kit Type 1075
- Adobe PostScript3
- Memory (256 MB required for printing)
 - 128 MB
 - 256 MB
- DeskTopBinder

Features

- | | | | | |
|-----------------------|----------------------------------|------------------------------------|-------------------------|--------------------|
| ■ Auto Image Density | ■ Copy Counter | ■ Electronic Sort | ■ Original Counter | ■ Stamping |
| ■ Auto Paper Select | ■ Delete Inside/Outside | ■ Energy Saver Mode | ■ Paper Designate | ■ User Codes (500) |
| ■ Auto Reduce/Enlarge | ■ Directional Size Magnification | ■ Estimated Finishing Time Counter | ■ Photo Mode | ■ User Program |
| ■ Auto Start | ■ Document Server | ■ Image Shift | ■ Repeat Copy | ■ User Tools |
| ■ Auto Tray Switching | ■ Double Copy | ■ Job Interrupt | ■ Sample Copy | ■ Weekly Timer |
| ■ Border/Center Erase | ■ Dual Language | ■ Job Preset (up to 8 jobs) | ■ Scan Once, Print Many | |
| ■ Chapters | ■ Duplexing | ■ Margin Adjustment | ■ Series Copying | |
| ■ Combine Originals | | | ■ Slip Sheets | |

RICOH®

Image Communication

Ricoh Corporation, Five Dedrick Place, West Caldwell, NJ 07006
 Phone: (973) 882-2000 • Web Site: <http://www.ricoh-usa.com>



EPA 2000 Office Products Partner of the Year (5th consecutive year)
EPA 2000 Labeling Partner of the Year

Ricoh Corporation has determined that this product meets the Energy Star® guidelines for energy efficiency.

Ricoh Company, Ltd. has been granted a certificate of ISO 9001, which is the International Standard for Quality Systems.

Printed in U.S.A. on recycled paper because Ricoh cares.

OFFICIAL PRINTER,
 COPPER AND FAX
 OF THE PEW OF AMERICA



Adobe® PostScript® 3

CA-0220