

THE RICOH AFICIO AP3800CMF

Re-defining the **multi-functional solution** for the workgroup!

Too many offices are cluttered with printers that do too little, copiers that cost too much, and fax machines that take up valuable space.

Now more than ever, you need a single system capable of satisfying all your document needs.

*The solution is here:
The Ricoh Aficio AP3800CMF*

copier,
scanner,
fax
**Color
Printer**



Ricoh now delivers the Aficio AP3800CMF, a multi-function device that does it all and keeps up with the frantic pace of today's business world. It's a digital color copier, a network scanner, a facsimile and a printer all in one.

Performance is unsurpassed on the AP3800CMF, with 38/28 ppm output (black & white/full color) for both printing and copying. Features like the Scan Once Print Many and RIP Once and Print Many on the AP3800CMF allow the engine to image at its full rated speed. This speed is not compromised even with two-sided output. Furthermore, document finishing is easily accessed so that prints or copies can be collated and stapled for immediate distribution.

The AP3800CMF is a true information hub for your workgroup, capable of receiving, storing, forwarding, and distributing color and black & white documents in whatever format suits your needs—whether via e-mail or facsimile.

Copier

As a copier, the AP3800CMF produces an amazing **28 color and 38 black & white copies per minute**. Originals as large as **11" x 17" can be scanned** and, when configured with the optional ARDF, the AP3800CMF can copy up to 80 pages—front and back automatically. Combined with the optional finisher, the AP3800CMF can provide the final touches on copied and printed documents so that they have that professional appearance, ready for distribution.

Scanner

Organizing, annotating, and distributing your documents can be a simple process once they're digital. With the AP3800CMF's ability to **scan up to 600 dpi and 8 bits/pixel**, you can digitize a wide range of originals, including books, documents, line drawings and color images, with the ability to route the digital files to virtually anyone on the network. All popular file formats are supported, including PDF, TIFF, and JPEG.

Printer

The AP3800CMF comes with all of the printing capabilities and speed found on the AP3800C, including **1200 dpi resolution**, as well as PCL5c emulation, genuine Adobe PostScript 3 and Ricoh's new RPCS print drivers. Of course, automatic duplex printing and optional document finishing can be accessed through any of the print drivers.

Fax

The AP3800CMF can be outfitted with a fax option, which supports G3, but can be upgraded to G4, which supports up to 64k bps transmission rates. The AP3800CMF fax option delivers other fax capabilities like group dialing, page stamping, and quick dialing. In addition to providing all the features you've come to expect in a dedicated facsimile machine, the AP3800CMF **enables everyone on the network to send and receive faxes** without leaving their desk.

Document Server

As a document server, the AP3800CMF offers you the **ability to re-purpose documents**. All documents—whether faxed or copied on the AP3800CMF—are stored digitally on the system's 40 GB hard disk drive. You can then re-output, re-fax, or re-distribute these documents as many times as necessary.

Standard Ricoh Utilities that provide complete document management control.

DeskTopBinder Lite allows you to view documents stored on the AP3800CMF hard drive and re-purpose them. The optional upgrade to **DeskTopBinder Pro** includes OCR capabilities and the ability to view pages, regardless of the source application.

Job Binder is a unique feature within the Ricoh RPCS print driver that enables you to select specific pages from multiple documents, regardless of the application, and print them as one document, complete with new page numbering, titles, headers and footers. Job

Binder also enables you to apply duplex printing and any available finishing features like collating, stapling or hole punching.

ScanRouter Lite is the utility that turns the AP3800CMF into a network scanner. Hardcopy pages are digitized and then distributed to a client desktop. For more extensive distribution alternatives, Ricoh offers **ScanRouter Pro**, an optional dedicated server configuration, which enables scanned files to be distributed via e-mail beyond the immediate network segment. ScanRouter Pro also enables you to have inbound faxes redirected to an email address or server as a PDF or TIFF attachment. DeskTopBinder Pro is included with ScanRouter Pro.

SmartNetMonitor is Ricoh's peripheral monitoring and management utility. It provides a constant update of the default printer's status, whether it is available or busy with another print job. SmartNetMonitor also features Recovery Printing, so if the primary printer is unavailable, a print job can be automatically redirected to another Ricoh printer on the network to ensure output. Or if you have multiple sets of a document, the Parallel Printing feature enables you print multiple sets of a document using two or more Ricoh printers in tandem for greater productivity and use of the printing resources on the network.

The AP3800CMF—printing, copying, faxing, and scanning—at all at a price your organization can afford.

RICOH®

THE RICOH AFICIO AP3800CMF

General Specifications (EDP 400825)

Copy Function

Process:	Laser beam scanning, electro-photographic printing and dual component toner development
Originals:	Sheet / Book / Object
Scanning Area:	Max. 11" x 17"
Resolution:	Input: 600 dpi / 8 bits Output: 600 dpi / 2 bits
Gradation:	256 gradations
Copy Size:	Max. 11" x 17" (full-bleed on 12" x 18")
Paper Sizes:	Standard Trays: 8.5" x 11", 8.5" x 14", 11" x 17", 7.25" x 10.5", 8" x 13", 8.25" x 13", 8.5" x 13", A5, A4, A3 Bypass Tray: Width 4.0" to 12"; Length 5.8" to 18"
Warm-Up Time:	Less than 120 seconds
First Copy Speed:	Monochrome: 8 sec. (Letter-size, 1st Tray) Color: 10 sec. (Letter-size, 1st Tray)
Copy Speed:	Normal Mode (600 x 600 dpi) 38 cpm (b/w), 28 cpm (full color) OHP/Thick Paper Mode 10 cpm (b/w), 10 cpm (full color)
Multiple Copying:	Up to 99
Input Paper Capacity:	100-sheet Bypass Tray 500-sheet Paper Tray x 3
Output Paper Capacity:	Standard: 500 sheets plus 100 sheet Face-up Tray Optional Multi-bin: 350 sheets Optional Finisher: 2,500 sheets
Paper Weight:	Trays: 16 to 28 lb. bond Bypass Tray: 16 lb. bond to 90 lb. index
Paper Type:	Plain paper, laser printer qualified transparencies, cardstock, labels
Reproduction Ratios:	6 Reductions, 5 enlargements (400%, 200%, 155%, 129%, 121%, 100%, 85%, 78%, 73%, 65%, 50%, 25%)
Zoom:	From 25% to 400% in 1% Steps
Auto Duplex Copy:	Standard
Duty Cycle:	200,000
Memory:	192 MB RAM; 384 MB max.
Memory Type:	144 pin DIMM; SDRAM (PC100 compliant)
Hard Disk Drive:	40 GB

Advanced Copy Features

Color Selections:	Full Color; Black & White; Single Color; Twin Color
Single Color:	Preset Color Pallet: 12 colors with 4 levels of density selection User Color Memory: 15 colors
Twin Color:	Black + One Single Color Black + Red
Original Selection:	Auto Text and Photo Separation Mode; Photo Mode (includes selection of Press Print, Glossy Photo, or 2nd Generation Modes); Text Mode; Map Mode; Second Generation Mode; Pale Mode
Image Density Adjustment:	Auto/Manual (9 steps)
Reduce/Enlarge:	Auto Magnification Selection; Directional Magnification
Image Rotation:	90° rotation
Shift/Erase Image:	Centering; Margin Adjustment; Erasing Center; Erasing Border; Erasing Center / Border
OHP Slip Sheet:	Yes
Image Color Adjustment:	Auto Color Calibration; Color Balance; Color Separation; Sharp/Soft; Contrast; Background Density Control; UCR; Auto Text and Photo Separation
Proof Copy:	Yes
Operation Panel:	Monochrome LCD

Scanning Features

Resolution:	Up to 600 dpi (default setting at 200 dpi)
First Scanning Speed:	Less than 6 seconds
Drivers:	Network Twain version 1.7 or later
Scanning Utility:	ScanRouter Lite

Printer Features

CPU:	RM7000 300MHz
Printer Languages:	PCL5c emulation, Adobe PostScript 3, Ricoh RPCS
Resolution:	True 1,200 x 1,200 dpi; 1,200 x 600 dpi; 600 x 600 dpi
Fonts:	For PCL - 35 Intellifonts, 10 TrueType Fonts, 1 Bitmap Font For PS - 136 Adobe Type 1 Fonts
Interface:	10/100 BaseTX Ethernet and Bi-directional IEEE 1284-compliant parallel
Optional Interface:	IEEE 1394
Network Protocols:	TCP/IP, IPX/SPX (NetWare 3.x, 4.x, 5.x), EtherTalk, NetBEUI, and IPP (Internet Printing Protocol)
Utilities:	DeskTopBinder Lite, SmartNetMonitor
Drivers:	PCL5c: Win 95 / 98 / Me / NT4.0 / 2000 / XP PS: Win 95 / 98 / Me / NT4.0 / 2000 / XP, Mac 7.6.1 or later RPCS: Win 95 / 98 / Me / NT4.0 / 2000 / XP

Physical Specifications

Dimensions (W x D x H):	28.8" x 30.4" x 51.3"
Weight:	271.1 lbs.
Power Requirements:	120V 12A, 60Hz
Power Consumption:	1,440W or less

Optional Accessories

Type 3800C Facsimile (EDP 400557)

Type:	G3 Transceiver
Optional Second Line:	G3 (EDP 400560) G4 (EDP 400562)
Circuit:	PSTN, PBX, optional ISDN
Resolution:	200 x 200 dpi; 200 x 100 dpi
Scanning Speed:	approx. 0.7 seconds/page
Modem Speed:	33,600 bps - 2,400 bps with automatic shutdown
Transmission Speed:	3.0 seconds
Compression Method:	MH / MR / MMR (JBIG optional)
SAF Memory:	2 MB; Optional 32 MB

Automatic Reversing Document Feeder DF73 (EDP 400554)

Original Size	8.5" x 11" to 11" x 17"
Original Weight	16 to 32 lb.
Stack Capacity	80 sheets (20 lb. bond)
Speed	Scanning: 30 spm monochrome; 20 spm full color with HDD at 200 dpi Copying: 38 spm monochrome; 28 spm full color Note: Either ARDF or Platen Cover must be selected

Platen Cover Type 3800C (EDP 400571)

Note: Either ARDF or Platen Cover must be selected

PT460 Multi-bin (EDP 400568)

Number of bins:	2
Paper Size:	5.5" x 8.5" to 11" x 17"
Paper Weight:	16 to 28 lb.
Stack Capacity:	Tray 1 100 sheets 20 lb. bond Tray 2 250 sheets 20 lb. bond (8.5" x 11") 100 sheets 20 lb. bond (8.5" x 14"/11" x 17") Note: Cannot be installed simultaneously with SR770 Finisher

SR770 Finisher (EDP 400542)

Upper Tray	Paper Sizes: 8.5" x 11" to 11" x 17" Paper Weight: 16 to 28 lb. bond Stack Capacity: 500 sheets (8.5" x 11") 250 sheets (8.5" x 14"/11" x 17") Note: Cannot be installed simultaneously with PT460 Multi-bin
Lower Tray	Paper Sizes: 8.5" x 11" to 11" x 17" Paper Weight: 16 to 28 lb. bond Stack Capacity: 2,000 sheets (5.5" x 8.5" to 8.5 x 11) 750 sheets (11" x 17")
Staple Capacity:	50 sheets (8.5" x 11", 20 lb. or 30 sheets (11" x 17", 20 lb.)
Staple Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17"
Staple Paper Weight:	17 to 23 lb. bond
Number of Staples:	5,000/cartridge

Punch Kit Type 1045 (EDP 410785)

Number of Holes:	Two or Three
Paper Size:	8.5" x 11", 11" x 17", A4, A3
Paper Weights:	16 to 28 lb. bond Note: Punch is compatible with SR770 Finisher only

IEEE 1394 Interface Board Type 1045 (EDP 410716)

Included Cables:	2.0m 6pin to 6pin cable, 2.0m 6pin to 4pin cable
Hardware Specifications:	6pins; 2 ports available
Data Transmission Speed:	100/200/400 Mbps
System Requirements:	Windows 2000 Professional / Server with Service Pack 1 Minimum 128 MB memory is required.

Memory Options:

144-pin DIMM; SDRAM (PC100 compliant)
128 MB (EDP 001025MIU), 256 MB (EDP 001103MIU)

Supplies (yields based upon 5% coverage on letter sized page)

Black Toner (EDP 888030) @ Approx. 20,000 pages
Cyan Toner (EDP 888037) @ Approx. 10,000 pages
Magenta Toner (EDP 888036) @ Approx. 10,000 pages
Yellow Toner (EDP 888035) @ Approx. 10,000 pages
Black PCU (EDP 400548)
Color PCU (EDP 400594)
Black Development Unit (EDP 400661)
Color Development Units (EDP 400595)
Waste Toner Bottle (EDP 400662)
Fusing Unit (EDP 400596)
Oil Supply Unit (EDP 400549)
Paper Feed Rollers (EDP 400576)
Staple Set Cartridge Type K (EDP 410801) @ 5,000 shots
Staple Refills Type K (EDP 410802) @ 5,000 x 3 shots

Specifications and external appearances are subject to change without notice.
For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.
Print speed may be affected by network, application or PC performance.
Products are shown with optional features.

Designed for



Windows® 98



EPA 2000 Office Products Partner of the Year (5th consecutive year)
EPA 2000 Labeling Partner of the Year
Rico Corporation has determined that this product meets the Energy Star® guidelines for energy efficiency.

Windows® and Windows® 3.1/95/98/Me/NT4.0/2000/XP are registered trademarks of Microsoft Corporation. Macintosh®, Mac OS and AppleTalk® are registered trademarks of Apple Computer, Inc. Adobe® and PostScript® are trademarks of Adobe Systems, Inc. PCL® is a registered trademark of Hewlett-Packard Company. Ricoh® and Aficio® are registered trademarks of Ricoh Company, Ltd. RPCS™ is a trademark of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.

RICOH®

Ricoh Corporation, Five Dedrick Place, West Caldwell, NJ 07006
Phone: (973) 882-2000 • Website: <http://www.ricoh-usa.com>